

Specification

Curve Lighting System

AS3535-30A45





AS3535-30A45



Features

- Various installation ways: pendant, recessed and surface mounted
- Ever-changing shapes generated by means of super free application and connections of lines and arcs
- Flexible diffuser making it easy for installation without connections for over length application and light leakage
- Specially designed light source with diffusers producing homogeneous and soft lighting
- AL6063-T5 aluminum profile with high-quality surface treatment and three optional colors of black, white and silver








Details





Optional Accessories

Picture	Item	Parameter
	①Profile	Material : AL6063-T5 Profile weight : 0.95kg/ D3000mm , 45° Size : 35x35mm , D3000mm , 45° Surface processing: Spray
	②Cover	Size : L20000*W32*H3.5mm Light transmittance: 60%
	③End cap	Size : L35*W35*H1.5mm
	④Rigid modular DY8140-24V-20mm-30A23	Material :AL,CCT:1900/2300/2700/3000/3500/4000/5000/6000K ; CRI > 80 ; Voltage : 24V ; Power : 11.6W/pcs ; Lumen : 1300Lm/m ; Width : 20mm ; Minimum cutting unit : 14LEDs ;
	⑤Screw set	Size : M3.5*40mm

Picture	Item	Parameter
	Pendant cable PN-WA2/4	Steel cable: D1.5*2000/4000mm/maximum load bearing:13Kg
	Pendant cable PN-CA2/4	Size:20AWG\2000mm\maximum load bearing:6.5Kg
	Recessed buckle RE-13	Size : L78*W34*H15mm
	Connect fitting EX-26	Size : L30*W23.5*H4.6mm
	Surface mounted buckle CL-05	

Optical Parameter

AS3535-30A45 module/DY8140-24V-20mm-30A23 light source, frosted diffuser



Package



Components	Packaging material	Size(mm)	NW(kg)	GW(kg)	Content
30A45	Hat box	1245*305*158mm	21.24	24.24	18pcs/box