


Specification

Integrated Furniture Lighting

1911C



1911C




Features


DLS1.0, a special local auxiliary lighting system, can be widely used in various interior decoration scenarios and local light spaces. A touch of auxiliary decorative lighting in addition to the basic lighting creates different atmospheres and visual enjoyment.

Embellish life with light that follows you whenever you go.




- 1、 “Dots-free”lighting
Perfect homogenous lighting.
- 2、 Various diffuser options
Several options of diffusers, In various shapes and light distribution plans Complete with everything needed
- 3、 “Two” end caps
Two options of end cap for two ways of wire outgoing, Close-fitting design without screws makes installation much easier
- 4、 Various installation methods
A wide range of installation accessories wider applications
- 5、 “One” cut
Consistent length between diffuser and profile
- 6、 Smart control for unlimited possibilities
Perfectly match the profiles like customized, Control by hand sweep or touching









Details



Standard Configuration



Picture	Item	Parameter
	①Profile	Material: AL6063-T5 Profile weight: 0.56kg/2.5m Size : L2500*W19.7*H11mm Surface processing: Anodizing
	②Cover	Type: Frosted diffuse Material: PC Light transmittance : 85% Size : L2500*W19.7*H10.6mm (shrink) 0.8mm/m when the temperature rises (drops) 10°C.
	③End caps	Size : L19.7*W19.6*H5mm

Optional Accessories

Picture	Item	Parameter
	④FPC strip D6280-24V-10mm	Material : FPC , CCT : 2700/3000/4000/6000K ; Ra > 90; Voltage:24V ; Power : 15W/m ; Lumen : 1508Lm/m ; PCB width : 10mm ; Minimum cut : 50mm ;
	⑤End cap with hole	Size : L19.7*W19.6*H5mm
	⑥Clips	Size : L38*W15*H4.5mm
	Pendant-with junction box	Cord:D1.5*2000mm(D1.5*4000mm) Box:L80*W80*H30mm
	Pendant-without junction box	Cord:D1.5*2000mm(D1.5*4000mm)
	pendant-wire and line in one 2m/4m	

Optical Parameter

The testing result of 1M luminaire (with " D6280-24V-10mm " and diffuser)




Package

Mode 1 :



Mode 2 :



Components	Packaging material	Size(mm)	NW(kg)	GW(kg)	Content
Single piece	Hat box	2580*41*27.5mm	0.76	1.36	1pcs/box
Whole bundle	Hat box	2580*250*165mm	19	36	25pcs/box
Whole box packaging	Paper box	2580*95*100mm	6.84	9.84	9pcs/box