


# Specification

Integrated Furniture Lighting

LE2507



## LE2507



Example of application: furniture board  
Cutout:W18\*D7mm fixed by glass cement




### Features


DLS1.0, a special local auxiliary lighting system, can be widely used in various interior decoration scenarios and local light spaces. A touch of auxiliary decorative lighting in addition to the basic lighting creates different atmospheres and visual enjoyment.

Embellish life with light that follows you whenever you go.






- 1、 “Dots-free”lighting  
Perfect homogenous lighting.
- 2、 Various diffuser options  
Several options of diffusers, In various shapes and light distribution plans Complete with everything needed
- 3、 “Two” end caps  
Two options of end cap for two ways of wire outgoing, Close-fitting design without screws makes installation much easier
- 4、 Various installation methods  
A wide range of installation accessories wider applications
- 5、 “One” cut.  
Consistent length between diffuser and profile
- 6、 Smart control for unlimited possibilities  
Perfectly match the profiles like customized, Control by hand sweep or touching





## Details



## Standard Configuration



Picture	Item	Parameter
	①Profile	Material: AL6063-T5 Profile weight:0.29kg/2.5m Size: L2500*W25*H7mm Surface processing: Anodizing
	②Cover	Type: Frosted diffuse Material: PC Light transmittance: 60% Size: L2500*W14.7*H4.5mm (shrink) 0.8mm/m when the temperature rises (drops) 10°C.
	②Microprism diffuser	Type: Microprism diffuser Material: PC Light transmittance: 65% Size: L2500*W14.7*H4.5mm (shrink) 0.8mm/m when the temperature rises (drops) 10°C.
	②Black Microprism	Type: Black Microprism Material: PC Light transmittance: 15% Size: L2500*W14.7*H4.5mm (shrink) 0.8mm/m when the temperature rises (drops) 10°C.
	③End caps	Size: L25*W7*H10mm

## Optional Accessories

Picture	Item	Parameter
	④FPC strip D6280-24V-8mm	Material: FPC, CCT: 2700/3000/4000/6000K; Ra > 90; Voltage:24V; Power: 15W/m; Lumen: 1650Lm/m; PCB width: 8mm; Minimum cut: 25mm;
	⑤End caps	Size: L25*W7*H10mm


## Optical Parameter

The testing result of 1M luminaire (with " D6280-24V-8mm " and diffuser )




## Package

Mode 1 :



Mode 2 :



Components	Packaging material	Size(mm)	NW(kg)	GW(kg)	Content
Single piece	Hat box	Φ31mm*2580mm	0.42	0.86	1pcs/box
Whole bundle	Hat box	2580*250*165mm	13.86	30.38	33pcs/box
Whole box packaging	Paper box	2580*95*100mm	12.6	15.6	30pcs/box